

GIGA X3: Specifications

Recommended maximum daily output

Recommended maximum daily output	150
----------------------------------	-----

Areas of use

Catering	✓
----------	---

Coffee to Go	✓
--------------	---

Office floor solutions	✓
------------------------	---

Seminar/conference facilities	✓
-------------------------------	---

Breakfast room	✓
----------------	---

Specialities

Ristretto	✓
-----------	---

2 × Ristretto	✓
---------------	---

Espresso	✓
----------	---

2 × Espresso	✓
--------------	---

Coffee	✓
--------	---

2 × Coffee	✓
------------	---

Americano	✓
-----------	---

2 xAmericano	✓
--------------	---

Lungo	✓
-------	---

2 x Lungo	✓
Special coffee	✓
2 x Special coffee	✓
Espresso doppio	✓
Pot of coffee	✓
Cortado	✓
2 x Cortado	✓
Espresso macchiato	✓
2 x Espresso macchiato	✓
Caffè latte	✓
2 x Caffè latte	✓
Cappuccino	✓
2 x Cappuccino	✓
Flat white	✓
2 x Flat white	✓
Latte macchiato	✓
2 x Latte macchiato	✓
Portion of milk foam	✓
2 x Portion of milk foam	✓
Portion of milk	✓
2 x Portion of milk	✓

Hot water	✓
Hot water for green tea	✓
Hot water for black tea	✓
Ground coffee	✓

Specific benefits

Number of specialities	32
Speed function	✓
Automatic Grinder Adjustment (A.G.A.)	✓
Automatic switching between milk and milk foam	✓
Transmitter supplied as standard	Smart Connect

JURA coffee machine standards

Pulse Extraction Process (P.E.P.®)	✓
Lungo function	✓
Variable brewing unit	5 – 16 g
Grinder	Electronically adjustable ceramic disc grinder
High-performance pump, 15 bar	2
Thermoblock heating system	2
Fluid systems	2
Milk system / interchangeable milk spout	HP3 / CX2

Powder chute for ground coffee	✓
--------------------------------	---

Active bean monitoring	✓
------------------------	---

Operating and programming standards

Rotary Switch	✓
---------------	---

Display	4.3" touchscreen colour display
---------	---------------------------------

Position, duplicate and personalise products according to personal preference	✓
---	---

Individually programmable quantity of water for coffee	✓
--	---

Individually programmable coffee strength	10 levels
---	-----------

Individually programmable amount of milk/milk foam	✓
--	---

Individually programmable milk/milk foam temperature	10 levels
--	-----------

Individually programmable brewing temperature	3 levels
---	----------

Individually programmable hot water temperature	3 levels
---	----------

Intelligent Pre-Brew Aroma System with optional deactivation	✓
--	---

Generating code groups	✓
------------------------	---

Resettable day counter	✓
------------------------	---

Shows the number of preparations for each individual product	✓
--	---

Connectivity

Smart Connect	✓
---------------	---

Wi-Fi Connect ✓

Payment Connect ✓

Payment and telemetry systems

Pocket Pilot 2.0 ✓

Data Communicator ✓

Hygiene standards

Filter cartridge CLARIS Pro Smart maxi / CLARIS Pro Smart

One-Touch milk system cleaning (automatic) ✓

Integrated rinsing, cleaning and descaling programme ✓

Monitored drip tray ✓

JURA hygiene: TÜV-certified ✓

Energy standards

Energy Save Mode (E.S.M.©) ✓

Zero-Energy Switch or power switch ✓

Programmable switch-off time ✓

Programmable switch-on/switch-off time ✓

Design and materials

Alu Frame Design© 3 mm	✓
Centre panel in Piano Black	✓
Cup illumination	✓

In figures

Height-adjustable/width-adjustable dual spout	70 – 159 mm / –
Height-adjustable hot-water spout	69 – 165 mm
Water tank capacity	5 l
Bean container holding capacity	1 kg
Coffee grounds container (approx. servings)	40
Cable length	1.1 m
Voltage / power	230 V ~ / 2700 W
Current	10 A
Stand-by power	< 0,5 W
Weight	19 kg
Dimensions (W × H × D)	37 × 55.5 × 49.7 cm
Article number, product code	15666, Aluminium (INTB)
EAN code	7610917156665
Country of production	Made in Switzerland
Model year	2023

Supplied as standard

Measuring spoon for ground coffee	✓
Milk pipe including connector	✓
Container for milk system cleaning	✓
Milk system cleaner (mini tabs)	✓
3-phase cleaning tablets	✓
CLARIS Pro Smart+ filter cartridge	✓
Instructions for use	✓
Warranty conditions	✓
